



## (305mm) Open Coiled Lengths

Spring Number	Outside Diameter		Coils per Inch	Wire Diameter		
	Ins.	mm		SWG	Ins.	mm
MSL 401	0.19	4.80	15	26	0.018	0.45
MSL 402	0.19	4.80	16	24	0.022	0.56
MSL 403	0.19	4.80	17	22	0.028	0.71
MSL 404	0.25	6.40	11	23	0.024	0.61
MSL 405	0.25	6.40	13	21	0.032	0.81
MSL 406	0.25	6.40	14	19	0.040	1.00
MSL 407	0.31	8.00	9	22	0.028	0.71
MSL 408	0.31	8.00	10	20	0.036	0.91
MSL 409	0.31	8.00	12	18	0.048	1.20
MSL 410	0.38	9.50	7	20	0.036	0.91
MSL 411	0.38	9.50	9	18	0.048	1.20
MSL 412	0.38	9.50	9	16	0.064	1.60
MSL 413	0.44	11.0	6	19	0.040	1.00
MSL 414	0.44	11.0	7	17	0.056	1.40
MSL 415	0.44	11.0	8	15	0.072	1.80
MSL 416	0.50	13.0	6	18	0.048	1.20
MSL 417	0.50	13.0	6	16	0.064	1.60
MSL 418	0.50	13.0	7	14	0.080	2.00
MSL 419	0.75	19.0	4	15	0.072	1.80
MSL 420	0.75	19.0	4	13	0.092	2.30
MSL 421	0.75	19.0	5	11	0.116	2.90

Suitable for cutting into shorter lengths.  
 Box AC Containg 1 of each type MSL 401-421 Available